

Lotz Armor Edge™ Tops:

Lotz Armor Edge™ top is constructed of 1.125" thick MDF (medium density fiberboard) core. MDF is a superior material for screw holding abilities exceeding 250 lbs., breaking strength and load tests. The back material is phenolic which **prevents moisture penetration** to core material and provides an anti gum surface. High pressure laminate is bonded to the **MDF core**. The .25" beveled radius edge is finished using our exclusive Lotz Armor Edge™, a polyurea, which is extremely strong and durable. **This edge will not separate from the MDF core material and makes the edge water tight.** Armor Edge comes black standard. Colors available.



3mm Tops:


The core material is 1.125" thick particle board with a phenolic backer sheet and high pressure laminate on top. 3mm PVC edge banding is applied to all four sides, radius corners.



Optional top surface choices include **whiteboard laminate or chemical resistant laminate** and most Wilsonart matte (-60) finish laminates with possible up charges. Other vendors available upon request.

Shipping Class: 70
NMFC#: 83620-2

Frame Color Options:



Adjustable leg insert with 2 tamper resistant screws




Spanner bars available in multiple lengths

Available Options:




Steel book box (-LB)



Clear View tote tray (can interchange with tote storage unit) (-TB)



Full Color tote tray (can interchange with tote storage unit) (See catalog for color selection)



Wire Basket (-LW)



Backpack hook



Dual wheel locking casters (-CA)



2.5" Grand Hank glide (-HG)



Grommet hole (optional)

Legs:

The UNE-T adjustable legs are 1.25" square, 15-gauge steel tube with fully welded 10-gauge mounting plate. Legs attach to desk with 16 metal-to-metal inserts and screws. The lower leg section is fabricated to fit into the upper 1.25" square, 15-gauge leg assembly. Legs can adjust from 21" to 30"; these adjustments are connected to the upper leg with two drilled holes and then screwed into the punch holes of the lower leg for positive contact and safety with adjustability using M6-1x14 screws. Powder-coated smooth silver finish standard.

Leg is fitted with a non-marring adjusting glide with a .375"-16 stud with a 1" travel path.

Connector Bar:

1x2" 14-gauge steel tube with 14-gauge mounting tabs. Connect to legs with 4 .25"-20x15mm joint connector bolts.

UNE-T 2-Student Tables:

Lotz AE™ Top	Wgt	3mm Top	Wgt	D" x L"
UNE7138-ADJ	56	UNE6138-ADJ	54	20 x 48
UNE7143-ADJ	61	UNE6143-ADJ	59	20 x 54
UNE7139-ADJ	65	UNE6139-ADJ	64	20 x 60
UNE7140-ADJ	77	UNE6140-ADJ	75	20 x 72
UNE7069-ADJ	66	UNE6069-ADJ	61	24 x 48
UNE7070-ADJ	69	UNE6070-ADJ	67	24 x 54
UNE7071-ADJ	73	UNE6071-ADJ	74	24 x 60
UNE7072-ADJ	87	UNE6072-ADJ	85	24 x 72

UNE-T 2-Student Tables with Double T Legs:

Lotz AE™ Top	Wgt	3mm Top	Wgt	D" x L"
UNE7080-ADJ	73	UNE6080-ADJ	69	30 x 48
UNE7081-ADJ	81	UNE6081-ADJ	76	30 x 54
UNE7082-ADJ	86	UNE6082-ADJ	81	30 x 60
UNE7083-ADJ	99	UNE6083-ADJ	94	30 x 72

